

OUTRIGGER SPREADS AND LOADS

ALL DIMENSIONS AND WEIGHTS ARE APPROXIMATE

Boom Type	FRONT Outrigger Spread in Ft. In.	REAR Outrigger Spread in Ft. In.	FRONT to REAR Outrigger Spread in Ft. In.	MAX. FRONT Outrigger Load LBS.	MAX. REAR Outrigger Load LBS.	MAX. Outrigger Soil PSI FRONT / REAR w/o Dunnage	MAX. Outrigger Soil PSI FRONT / REAR with Dunnage
Schwing America Inc.							
20M Z	12' 8'	7' 1"	15' 4"	24,730	15,740	315 / 200	44 / 28
S 31 XT	20' 5"	18' 8"	24' 5"	39,700	30,900	203 / 69	158 / 54
S 39 SX	26'	21'	30' 2"	42,466	40,466	296 / 296	72 / 72
S 45/47 SX	27' 3"	27' 3"	29' 0"	58,500	56,200	362 / 102	348 / 98
KVM 52/55	31' 2"	31' 2"	34' 2"	60,000	60,000	220 / 104	220 / 104
S 58/61 SX	29' 2"	41' 1"	37' 9"	78,680	83,176	157 / 51	166 / 54
Putzmeister America, Inc.							
38Z-5	20' 8"	23' 11"	22' 11"	43,388	46,985		
TB 110	23' 1"	26' 9"	27' 5"	30,350	34,395		
Everdigm America, Inc.							
38CX-5	20' 8"	25' 3"	28' 10"				